

Domestic Water Inlet-Outlet Temp., °F	Boiler Water Inlet Temp., °F	SP / STP Series Model	Domestic Water		Boiler Water		
			GPM	Pressure Drop, PSIG	GPM	Outlet Temp., °F	Pressure Drop, PSIG
40-160	165	SPB-62D	10	1	54	143	8
		SPB-90D	14	1	56	135	8
		SPB-118D	19	1	79	136	8
		SPB-174D	24	1	80	129	8
		SPB-222D	27	1	81	125	8
	170	SPB-62D	14	1	54	139	8
		SPB-90D	18	1	56	131	8
		SPB-118D	25	1	79	132	8
		SPB-174D	30	1	80	125	8
		SPB-222D	34	1	81	120	8
	180	SPB-62D	21	1	54	133	8
		SPB-90D	25	1	56	126	8
		SPB-118D	35	1	79	127	8
		SPB-174D	41	1	80	119	8
		SPB-222D	45	1	81	113	8
	190	SPB-62D	26	1	54	132	8
		SPB-90D	31	1	56	124	8
		SPB-118D	43	1	79	125	8
		SPB-174D	50	1	80	115	8
		SPB-222D	55	1	81	109	8
	200	SPB-62D	31	1	54	131	8
		SPB-90D	37	1	56	121	8
		SPB-118D	51	2	79	123	8
		SPB-174D	59	2	80	112	8
		SPB-222D	64	2	81	105	8
	210	SPB-62D	36	2	54	130	8
		SPB-90D	42	2	56	120	8
		SPB-118D	58	2	79	122	8
		SPB-174D	67	2	80	110	8
		SPB-222D	72	2	81	103	8
220	SPB-62D	40	2	54	131	8	
	SPB-90D	47	2	56	119	8	
	SPB-118D	66	2	79	120	8	
	SPB-174D	74	2	80	109	8	
	SPB-222D	80	3	81	101	8	
40-170	175	SPB-62D	10	1	54	151	8
		SPB-90D	13	1	56	145	8
		SPB-118D	18	1	79	145	8
		SPB-174D	23	1	80	138	8
		SPB-222D	27	1	81	132	8

Domestic Water Inlet-Outlet Temp., °F	Boiler Water Inlet Temp., °F	SP / STP Series Model	Domestic Water		Boiler Water		
			GPM	Pressure Drop, PSIG	GPM	Outlet Temp., °F	Pressure Drop, PSIG
40-170	180	SPB-62D	14	1	54	146	8
		SPB-90D	18	1	56	138	8
		SPB-118D	24	1	79	141	8
		SPB-174D	29	1	80	133	8
		SPB-222D	33	1	81	127	8
	190	SPB-62D	20	1	54	142	8
		SPB-90D	24	1	56	134	8
		SPB-118D	34	1	79	134	8
		SPB-174D	40	1	80	125	8
		SPB-222D	44	1	81	119	8
	200	SPB-62D	25	1	54	140	8
		SPB-90D	30	1	56	130	8
		SPB-118D	42	1	79	131	8
		SPB-174D	49	1	80	120	8
		SPB-222D	53	1	81	115	8
	210	SPB-62D	30	1	54	138	8
		SPB-90D	36	1	56	126	8
		SPB-118D	49	1	79	129	8
		SPB-174D	57	2	80	117	8
		SPB-222D	62	2	81	110	8
220	SPB-62D	34	1	54	138	8	
	SPB-90D	41	2	56	125	8	
	SPB-118D	56	2	79	128	8	
	SPB-174D	64	2	80	116	8	
	SPB-222D	69	2	81	109	8	
40-180	185	SPB-62D	10	1	54	159	8
		SPB-90D	13	1	56	153	8
		SPB-118D	18	1	79	153	8
		SPB-174D	23	1	80	145	8
		SPB-222D	26	1	81	140	8
	190	SPB-62D	14	1	54	154	8
		SPB-90D	17	1	56	148	8
		SPB-118D	24	1	79	147	8
		SPB-174D	29	1	80	139	8
		SPB-222D	33	1	81	133	8
	200	SPB-62D	20	1	54	148	8
		SPB-90D	24	1	56	140	8
		SPB-118D	33	1	79	142	8
		SPB-174D	39	1	80	132	8
		SPB-222D	43	1	81	126	8



SP SERIES: Double Wall- Brazed
40°F Inlet DHW

Domestic Water Inlet-Outlet Temp., °F	Boiler Water Inlet Temp., °F	SP / STP Series Model	Domestic Water		Boiler Water		
			GPM	Pressure Drop, PSIG	GPM	Outlet Temp., °F	Pressure Drop, PSIG
40-180	210	SPB-62D	24	1	54	148	8
		SPB-90D	29	1	56	138	8
		SPB-118D	41	1	79	137	8
		SPB-174D	48	1	80	126	8
		SPB-222D	52	1	81	120	8
	220	SPB-62D	29	1	54	145	8
		SPB-90D	34	1	56	135	8
		SPB-118D	48	1	79	135	8
		SPB-174D	55	2	80	124	8
		SPB-222D	60	2	81	116	8