

WATER HEATER CONTROLLER

FEATURES:

- 4.3 HMI Touchscreen
- Feedforward Logic Controller includes 1/8 DIN with LCD display (back-up interface)
- Data Logging
- Fault Log
- Trending/Graphing
- Compatibility with Modbus IP and BacNet IP BAS system standard without the need for external gateway.
- A gateway can be used for all other protocols



The NEW DHT state of the art control system offers unmatched performance and full user configurability for water heater applications. It features a durable temperature sensor transmitting a millivolt signal through quality twisted shielded wiring. The signal transmits directly into the advanced PID controller, which in turn sends a signal to the electrically activated fully modulating and fast acting control valve to achieve accurate temperature control over various demand situations. The controller has a 4.3-inch TFT color touchscreen user interface and is compatible with a Building Management System via ModBus IP or BacNet IP. Optional communications gateway is also available for RS485 communication.

Enclosure Dimensions	12"H x 10" W x 7" D
Display	4.3" TFT Color LCD
Graphics Display Resolution/ Colors	480 x 272 pixels w/ 65,536 display colors
Backlight	White LED, service life 50,000 hours and 24hr operation
Brightness control	16 Levels (Adjusted with touch panel)
Operating Mode	Single Tone, Visual Indicator
Memory:	8Gb
Supply Voltage	120/240 VAC
Certifications	NEMA 4, UL

DHT can accept no responsibility for possible errors in catalogs, brochures, and other printed material. DHT reserves the right to alter its products without notice. DHT and the DHT logotype are trademarks of DHT. All rights reserved.